



		RM-4010 (push)	RM-4110 (slide)
RecMic II			
Overall Frequency Response		200 - 9,000Hz	200 - 9,000Hz
Microphone Sensitivity		-39dBV	-39dBV
Microphone Sensitivity difference		Conference 0dB Dictation -12dB Voice Recognition -18dB Variable -7 to -56.5dB (Selectable from SDK)	
Maximum Output		350mW	350mW
Microphone/Speaker diameter		8mm/28mm	8mm/28mm
Input Level		+86dB SPL(-48dBv)	+86dB SPL(-48dBv)
Power Consumption (Current)		Standard mode: 278mA or less Low power mode: 80mA or less	Standard mode: 282mA or less Low power mode: 90mA or less
Mouse Function		✓	✓
Function Buttons		✓(4)	✓(4)
Record LED		✓(R/G/B)	✓(R/G/B)
Insert/Over Write LED		✓(R/G/B/PU)	✓(R/G/B/PU)
LED Blink		✓	✓
Beep		✓	✓
Triger Button in the Back		✓	✓
Trackball Click Function		✓	✓
Low power USB Device		✓	✓
Antimicrobial Housing		✓	✓
Alcohol wipe		✓	✓
Microphone		Omni-Directional	Omni-Directional
Dual microphone		✓	✓
USB	Storage	-	-
	Audio	✓	✓
	HID mouse	✓	✓
	HID keyboard	✓	✓
	Speed	USB2.0 Hi-Speed	USB2.0 Hi-Speed
Accessories	cradle	-	-
	stand	✓	✓
	holder	-	-
OS	Windows	Windows Vista/7/8.1/10	Windows Vista/7/8.1/10
	Mac	Mac OS X 10.5-10.12	Mac OS X 10.5-10.12
Device Management Software		✓*1	✓*1
DNS Commanad		✓	✓
Hotkey Command		✓	✓
Text Command		✓	✓
Application Launcher Command		✓	✓
Wait Command		✓	✓
Button Function Change		✓	✓
Slide Function Change		✓	✓
Mouse Speed		✓	✓
Beep Sound		✓	✓
Button Noise Suppression		✓	✓
Start Up Wizard		✓	✓
Click lock function		✓	✓
Cable Length		2.5m	2.5m
Dimensions(mm)		171x43.2x32mm	171x43.2x32mm
Weight(g)		185g(including cable)	185g(including cable)
*1 CD is not included. Device Configuration Manager can be downloaded from Web site.			